

**HIGH GLOSS**  
COLLECTION

—by Somerset™—



NATURAL RED OAK  
Red Oak

BUTTERSCOTCH  
Red Oak

GUNSTOCK  
Red Oak

CHERRY OAK  
Red Oak

NATURAL WHITE OAK  
White Oak

APPALACHIAN OAK FLOORING  
WITH A HIGHER GLOSS FINISH  
WILL MAKE YOUR SPACE SHINE.



**S SOLID**  
3/4" thick, random lengths up to 6-1/2'  
WIDTHS: 2-1/4", 3-1/4"



PRODUCT SPECIFICATION SHEET

02/19

# HIGH GLOSS: SOLID



Product:	Somerset <b>High Gloss Collection</b> Solid Hardwood Flooring			
Species:	Red Oak or White Oak (Somerset does not mix species.)			
Grade:	Proprietary Somerset grade			
Dimensions:	<b>Thickness:</b> 3/4"* <b>Widths:</b> 2-1/4", 3-1/4" <b>Lengths:</b> Random from 10" up to 6-1/2' <small>*Nominal</small>			
Construction:	Traditional 3/4" solid construction produced from domestically grown and harvested Appalachian hardwood. Material conforms to Appalachian Hardwood Manufacturers, Inc.'s Verified Sustainable Seal ( <a href="http://www.appalachianwood.org">www.appalachianwood.org</a> ). Product is also affiliated with the National Wood Flooring Association.			
Profile:	Eased Edge, Square End			
Finish:	Ultimate™ Urethane Finish—UV Cured Aluminum Oxide, Abrasion Resistant Finish			
Colors:	<b>2 1/4" Width</b>	<b>3 1/4" Width</b>	<b>Species</b>	
	Natural Red Oak	PS2601HG	PS3601HG	Red Oak
	Butterscotch	PS2603HG	PS3603HG	Red Oak
	Gunstock	PS2604HG	PS3604HG	Red Oak
	Cherry Oak	PS2605HG	PS3605HG	Red Oak
	Natural White Oak	PS2606HG	PS3606HG	White Oak
Gloss Level:	High Gloss			
Janka Hardness:	<b>Species</b>	<b>Lbs</b>		
	Red Oak	1290		
	White Oak	1360		
MSDS:	Not required for cured finish, MSDS for Wood Dust available on request			
Installation:	Nail down or staple, on or above grade. (NWFA Installation Guidelines and Methods, revised: March, 2019.) Installation guidelines are available at <a href="http://www.somersetfloors.com">www.somersetfloors.com</a>			
Maintenance:	Somerset Ultimate™ Wood Floor Cleaner ( <a href="http://www.somersetfloors.com">www.somersetfloors.com</a> )			
Limited Warranty:	50-Year Finish Wear; Lifetime Structural Integrity ( <a href="http://www.somersetfloors.com">www.somersetfloors.com</a> )			
Molding:	Quarter Round, Stair Nose, Threshold, T-Mold, and Reducer			