

**SPECIALTY
COLLECTION**

—by Somerset™—



									
HICKORY NATURAL	HICKORY MOONLIGHT	HICKORY SPICE	HICKORY NUTMEG	MAPLE NATURAL	MAPLE GREYSTONE	MAPLE TUMBLEWEED	MOUNTAIN BROWN	COUNTRY NIGHT	RUSTIC GREY
Hickory	Hickory	Hickory	Hickory	Maple	Maple	Maple	Red Oak	Red Oak	Red Oak

A COLLECTION OF APPALACHIAN SPECIES THAT
OFFERS UNIQUE STYLE AND DESIGN OPTIONS



S SOLID

3/4" thick, random lengths up to 6-1/2'
WIDTHS: 2-1/4"(maple), 3-1/4", 4", 5"
RANDOM WIDTHS: 2-1/4" – 3-1/4" – 4"

S SOLIDPLUS® ENGINEERED

1/2" thick, 3mm thick wear layer, 8-ply,
random lengths up to 6-1/2'
WIDTHS: 3-1/4", 5"
RANDOM WIDTHS: 3-1/4" – 5" – 7"



PRODUCT SPECIFICATION SHEET

04/17

SPECIALTY: SOLID



Product:	Somerset Specialty Collection Solid Hardwood Flooring				
Species:	Hickory & Red Oak (Somerset does not mix species.)				
Grade:	Proprietary Somerset grade				
Dimensions:	Thickness: 3/4"* Widths: Hickory: 3-1/4", 4", 5" Random Widths: Oak: 2-1/4" – 3-1/4" – 4" Lengths: Random from 10" up to 6-1/2' <small>*Nominal</small>				
Construction:	Traditional 3/4" solid construction produced from domestically grown and harvested Appalachian hardwood. Material conforms to Appalachian Hardwood Manufacturers, Inc.'s Verified Sustainable Seal (www.appalachianwood.org). Product is also affiliated with the National Wood Flooring Association.				
Profile:	Eased Edge, Eased End				
Finish:	Ultimate™ Urethane Finish—UV Cured Aluminum Oxide, Abrasion Resistant Finish				
Colors:	2 1/4" Width Strip	3 1/4" Width Strip	4" Width Plank	5" Width Plank	Species
	Hickory Natural	PS314HCB	PP41HCB	PP51HCB	Hickory
	Hickory Moonlight	PS314HMLB	PP41HMLB	PP51HMLB	Hickory
	Hickory Spice	PS314HSPB	PP41HSPB	PP51HSPB	Hickory
	Hickory Nutmeg	PS314HNUB	PP41HNUB	PP51HNUB	Hickory
	2 1/4" – 3 1/4" – 4" Random Width Plank				Species
	Mountain Brown	PPRWMBB			Red Oak
	Country Night	PPRWCNB			Red Oak
	Rustic Grey	PPRWRGB			Red Oak
Gloss Level:	Hickory: Semi Gloss Oak: Low Gloss				
Janka Hardness:	Species	Lbs			
	Hickory	1820	Red Oak	1290	
MSDS:	Not required for cured finish, MSDS for Wood Dust available on request				
Installation:	Nail down or staple, on or above grade. (NWFA Installation Guidelines and Methods, revised: March, 2019.) Installation guidelines are available at www.somersetfloors.com				
Maintenance:	Somerset Ultimate™ Wood Floor Cleaner (www.somersetfloors.com)				
Limited Warranty:	50-Year Finish Wear; Lifetime Structural Integrity (www.somersetfloors.com)				
Molding:	Quarter Round, Stair Nose, Threshold, T-Mold, and Reducer				

SPECIALTY: SOLIDPLUS® ENGINEERED



Product:	Somerset Specialty Collection Solid PLUS Engineered Hardwood Flooring			
Species:	Hickory, Hard Maple, or Red Oak (Somerset does not mix species.)			
Grade:	Proprietary Somerset grade			
Dimensions:	Thickness: 1/2"*; 3mm* thick solid dry sawn wear layer Widths: 3-1/4", 5" Random Widths: Oak: 3-1/4" – 5" – 7" Lengths: Random from 10" up to 6-1/2' <small>*Nominal</small>			
Construction:	8-ply cross-grain engineered construction; 7-ply birch core.			
Profile:	Eased Edge, Eased End			
Finish:	Ultimate™ Urethane Finish—UV Cured Aluminum Oxide, Abrasion Resistant Finish			
Colors:		3/4" Width	5" Width	Wear Layer Species
	Hickory Natural	EP314SPHCE	EP512SPHCE	Hickory
	Hickory Moonlight	EP314SPHME	EP512SPHME	Hickory
	Hickory Spice	EP314HSPE	EP512HSPE	Hickory
	Hickory Nutmeg	EP314HNUE	EP512HNUE	Hickory
	Maple Natural	EP314SPMPE	EP512SPMPE	Hard Maple
	Maple Greystone	EP314SPMGE	EP512SPMGE	Hard Maple
	Maple Tumbleweed	EP314TUME	EP512TUME	Hard Maple
		3/4" – 5" – 7" Random Width Plank		Wear Layer Species
	Mountain Brown	EPRWMBE		Red Oak
Country Night	EPRWCNE		Red Oak	
Rustic Grey	EPRWRGE		Red Oak	
Gloss Level:	Hickory, Maple: Semi Gloss Oak: Low Gloss			
Janka Hardness:	Species	Lbs		
	Hickory	1820	Red Oak	1290
	Hard Maple	1450		
MSDS:	Not required for cured finish, MSDS for Wood Dust available on request			
Formaldehyde Emissions:	ASTM D6007; BQL (below quantification limit—.008ppm) TSCA Title VI Compliant			
Critical Radiant Flux (CRF):	ASTM E648 (0.33 critical radial flux)			
Installation:	Nail, staple, glue down, or float on, above or below grade (ground level). (NWFA Installation Guidelines and Methods, revised: March, 2019) Installation guidelines are available at www.somersetfloors.com			
Maintenance:	Somerset Ultimate™ Wood Floor Cleaner (www.somersetfloors.com)			
Limited Warranty:	50-Year Finish Wear; Lifetime Structural Integrity (www.somersetfloors.com)			
Molding:	Quarter Round, Stair Nose, Threshold, T-Mold, and Reducer			